

Our focus is innovating security
where you need it most



IP Video product overview
January 2016



BOSCH
Invented for life

Table of Contents

Dome Cameras	4
Panoramic Cameras	11
Fixed Cameras	12
Specialty Cameras	16
Moving Cameras	18
Digital Recording	22
Digital Storage	24
Video Software	26
Viewing Software	28
Encoders and Deconders	29
Transcoders	30
Flat panel monitors	31

Added value for you

Intelligent Dynamic Noise Reduction

Quiet scenes with little or no movement require a lower bitrate. By intelligently distinguishing between noise and relevant information, such as movement, Intelligent Dynamic Noise Reduction reduces bitrate by up to 50%. And because noise is reduced at the source during image capture, the lower bitrate does not compromise video quality. With Intelligent Dynamic Noise Reduction, our focus is to significantly reduce storage costs, and lessen network strain by only using bandwidth when needed.

Intelligent Auto Exposure

Fluctuations in backlight and front light can ruin your images. To achieve the perfect picture in every situation, Intelligent Auto Exposure automatically adjusts the exposure of the camera. It offers superb front light compensation and incredible backlight compensation by automatically adapting to changing light conditions. With Intelligent Auto Exposure, our focus is to provide you with perfect exposure every time.

Intelligent Tracking

In video surveillance, moving objects are usually the most significant objects of interest. Intelligent Tracking automatically tracks moving objects based on predefined alarm rules or a simple click. By intelligently distinguishing between single and multiple reference points, Intelligent Tracking will provide uninterrupted tracking. Optimal capture of the object of interest is assured by dynamically adjusting the field of view. With Intelligent Tracking, our focus is never to lose track of objects of interest.

Intelligent Video Analysis

After only 20 minutes you can miss 90% of the activity on a screen. Intelligent Video Analysis assists by alerting you when predefined alarms are triggered. By smartly combining up to 8 rules, complex tasks are made easy and false alarms are reduced to a minimum. Intelligent Video Analysis also adds sense and structure to your video by adding metadata. This enables you to quickly retrieve the relevant images from hours of stored video. Metadata can also be used to deliver irrefutable forensic evidence or to optimize business processes based on, for example, people counting or crowd density information. With Intelligent Video Analysis, our focus is to alert you when needed and help you quickly retrieve the correct data.

starlight

All starlight cameras offer best in class light sensitivity, excellent wide dynamic range, and superb front and backlight compensation. The starlight cameras capture images up to 5 megapixel resolution even under extreme low-light conditions. They offer amazing images in fine detail. The latest sensor technology, combined with the sophisticated noise suppression, results in an amazing sensitivity. With an incredibly high frame rate of up to 60 frames per second, you can capture fast moving objects in high resolutions. With their impressive technical specifications, they could be the ultimate 24/7 cameras. With the starlight family, our focus is to make darkness totally visible.

4K ultra HD

Covering a large area and identifying objects at a great distance is challenging. That's why the 4K ultra HD technology in our DINION IP ultra 8000 MP offers 12 megapixel resolution to deliver amazing detail even when zoomed-in. With an incredibly high frame rate of 20 frames per second for a 12 megapixel camera, you can capture fast moving objects in high resolutions. This speed and these resolutions provide the level of detail that makes the difference when collecting evidence. The images produced are perfect for a detailed and effective retrospective analysis. The camera's ability to give a wide-angle overview and multiple focus points on a single screen helps you focus on details without losing the bigger picture. With the DINION IP ultra 8000 MP, our focus is to enable you to see every detail, everywhere.

IP Video

Dome Cameras

► FLEXIDOME IP micro 2000

► FLEXIDOME IP micro 5000



■ Available – Not available

Commercial Type Number		NUC-21002-F2	NUC-21012-F2	NUC-51022-Fxx	NUC-51051-Fxx
Bosch USPs	Intelligent Dynamic Noise Reduction (IDNR)	■	■	■	■
	Intelligent Auto Exposure (IAE)/Intelligent Defog	-/-	-/-	-/-	-/-
	starlight (extreme low-light sensitivity)	-	-	-	-
	4K ultra HD	-	-	-	-
	Built-in Intelligent Video Analysis (IVA)	-	-	-	-
Basic features	Maximum resolution	VGA	HD 720p	HD 1080p	5 MP
	Image sensor type	1/4"	1/4"	1/2.7"	1/3"
	Max. frames per second (fps)	30 fps@ 480p	30 fps@ 720p	30 fps@ 1080p	12 fps@ 5MP
	Indoor/outdoor/in-vehicle	■/-/■	■/-/■	■/■/■	■/■/■
	Day/night	■ (electronic)	■ (electronic)	■ (electronic)	■ (electronic)
	Wide Dynamic Range (WDR)	76dB	76dB	76dB	65dB
	ONVIF conformant	■	■	■	■
	Built-in microphone	■	■	-	-
	Power over Ethernet (PoE)	■	■	■	■
	Advanced features	Compression (H.264 & MJPEG)/multi-streaming	■/4 streams	■/4 streams	■/4 streams
Privacy masking		■	■	■	■
Region Of Interest tracking		-	-	-	-
Alarm triggering	Tamper detection	■	■	■	■
	Video motion detection	■	■	■	■
	Intelligent Video Analysis (IVA)	-	-	-	-
	Audio detection	■	■	-	-
Sensitivity	Minimum illumination day mode (color)	1 lux	1 lux	0.4 lux (F4) 1 lux (F2/F2M)	0.8 lux (F4) 2 lux (F2/F2M)
	Minimum illumination night mode (black/white)	-	-	0.4 lux (F4) 1 lux (F2/F2M)	0.8 lux (F4) 2 lux (F2/F2M)
	Night vision	-	-	-	-
	Max. range at night	-	-	-	-
	Lens	-	-	-	-
Automatic Back Focus (ABF)	-	-	-	-	
	Automatic varifocal	-	-	-	-
	Focal length	2.5 mm	2.5 mm	3.6 mm (F4) 2.5 mm (F2/F2M)	3.6 mm (F4) 2.5 mm (F2/F2M)
Horizontal Angle of View (HAoV)	66.7°	89°	97° (F4) 135° (F2/F2M)	74° (F4) 105° (F2/F2M)	
	DORI distances	Detect/Observe/Recognize/Identify (Distances in m according to EN-50132-7 standard)	24/10/5/2	26/10/5/3	34/13/7/3 (F4) 16/6/3/2 (F2)
Storage	Memory card slot	■ (up to 2 TB)	■ (up to 2 TB)	■ (up to 2 TB)	■ (up to 2 TB)
	Cloud application storage	Auto or Alarm JPEG Posting, Video Clips or JPEG Exporting	Auto or Alarm JPEG Posting, Video Clips or JPEG Exporting	Auto or Alarm JPEG Posting, Video Clips or JPEG Exporting	Auto or Alarm JPEG Posting, Video Clips or JPEG Exporting
Connections	Alarm input/output	-/-	-/-	-/-	-/-
	Audio in/out	-	-	-	-
	Hybrid*/confrontation monitor	-/■	-/■	-/■	-/■
Housing	Weather rating	-	-	IP66	IP66
	Vandal resistant	-	-	IK08	IK08
	Operating temperature	-20° to 50° C (-4° to 122° F)	-20° to 50° C (-4° to 122° F)	-30° to 50° C (-22° to 122° F)	-30° to 50° C (-22° to 122° F)

* The hybrid functionality offers an easy migration path from legacy CCTV to a modern IP-based system

IP Video

Dome Cameras

► FLEXIDOME IP indoor 4000 HD

► FLEXIDOME IP indoor 4000 IR

► FLEXIDOME IP outdoor 4000 HD

► FLEXIDOME IP outdoor 4000 IR



■ Available – Not available

Commercial Type Number		NIN-41012-V3	NII-41012-V3	NDN-41012-V3	NDI-41012-V3
Bosch USPs	Intelligent Dynamic Noise Reduction (IDNR)	■	■	■	■
	Intelligent Auto Exposure (IAE)/Intelligent Defog starlight (extreme low-light sensitivity)	- / ■	- / ■	- / ■	- / ■
	4K ultra HD	-	-	-	-
	Built-in Intelligent Video Analysis (IVA)	-	-	-	-
Basic features	Maximum resolution	HD 720p/1.3 MP (4:3)			
	Image sensor type	1/2.7"	1/2.7"	1/2.7"	1/2.7"
	Max. frames per second (fps)	30 fps@ 720p	30 fps@ 720p	30 fps@ 720p	30 fps@ 720p
	Indoor/outdoor/in-vehicle	■ / - / -	■ / - / -	■ / ■ / -	■ / ■ / -
	Day/night	■	■	■	■
	Wide Dynamic Range (WDR)	76dB	76dB	76dB	76dB
	ONVIF conformant	■	■	■	■
	Built-in microphone	■	■	-	-
	Power over Ethernet (PoE)	■	■	■	■
Advanced features	Compression (H.264 & MJPEG)/multi-streaming	■/4 streams	■/4 streams	■/4 streams	■/4 streams
	Privacy masking	■	■	■	■
	Region Of Interest tracking	-	-	-	-
Alarm triggering	Tamper detection	■	■	■	■
	Video motion detection	■	■	■	■
	Intelligent Video Analysis (IVA)	-	-	-	-
	Audio detection	■	■	■	■
Sensitivity	Minimum illumination day mode (color)	0.24 lux	0.24 lux	0.24 lux	0.24 lux
	Minimum illumination night mode (black/white)	0.05 lux	0 lux (IR on)	0.05 lux	0 lux (IR on)
	Night vision	-	■ (infrared)	-	■ (infrared)
	Max. range at night	-	15 m (50 ft)	-	15 m (50 ft)
Lens	Automatic Back Focus (ABF)	-	-	-	-
	Automatic varifocal	-	-	-	-
	Focal length	3.3 - 10 mm			
	Horizontal Angle of View (HAoV)	35.3° - 105.5°	35.3° - 105.5°	35.3° - 105.5°	35.3° - 105.5°
DORI distances	Detect/Observe/Recognize/Identify (Distances in m according to EN-50132-7 standard)	16-79/6-31/3-16/2-8	16-79/6-31/3-16/2-8	16-79/6-31/3-16/2-8	16-79/6-31/3-16/2-8
Storage	Memory card slot	■ (up to 2 TB)			
	Cloud application storage	Auto or Alarm JPEG Posting, Video Clips or JPEG Exporting	Auto or Alarm JPEG Posting, Video Clips or JPEG Exporting	Auto or Alarm JPEG Posting, Video Clips or JPEG Exporting	Auto or Alarm JPEG Posting, Video Clips or JPEG Exporting
Connections	Alarm input/output	1/1	1/1	1/1	1/1
	Audio in/out	■/■	■/■	■/■	■/■
	Hybrid*/confrontation monitor	■/■	■/■	■/■	■/■
Housing	Weather rating	-	-	IP66	IP66
	Vandal resistant	-	-	IK10	IK10
	Operating temperature	-20° to 50° C (-4° to 122° F)	-20° to 50° C (-4° to 122° F)	-30° to 50° C (-22° to 122° F)	-30° to 50° C (-22° to 122° F)

* The hybrid functionality offers an easy migration path from legacy CCTV to a modern IP-based system

IP Video

Dome Cameras

►FLEXIDOME IP indoor 5000 HD

►FLEXIDOME IP indoor 5000 MP



■ Available – Not available

Commercial Type Number		NIN-51022-V3	NIN-50022-A3	NIN-50051-A3
Bosch USPs	Intelligent Dynamic Noise Reduction (IDNR)	■	■	■
	Intelligent Auto Exposure (IAE)/Intelligent Defog starlight (extreme low-light sensitivity)	- / ■	- / ■	- / ■
	4K ultra HD	-	-	-
	Built-in Intelligent Video Analysis (IVA)	-	-	-
	Maximum resolution	HD 1080p	HD 1080p	5MP
Basic features	Image sensor type	1/2.7"	1/2.7"	1/3"
	Max. frames per second (fps)	30 fps@ 1080p	30 fps@ 1080p	12 fps@ 5MP
	Indoor/outdoor/in-vehicle	■/ - /-	■/ - /-	■/ - /-
	Day/night	■	■	■
	Wide Dynamic Range (WDR)	76dB	76dB	81dB
	ONVIF conformant	■	■	■
	Built-in microphone	■	■	■
	Power over Ethernet (PoE)	■	■	■
Advanced features	Compression (H.264 & MJPEG)/multi-streaming	■/4 streams	■/4 streams	■/4 streams
	Privacy masking	■	■	■
	Region Of Interest tracking	-	-	-
Alarm triggering	Tamper detection	■	■	■
	Video motion detection	■	■	■
	Intelligent Video Analysis (IVA)	-	-	-
	Audio detection	■	■	■
Sensitivity	Minimum illumination day mode (color)	0.24 lux	0.24 lux	0.35 lux
	Minimum illumination night mode (black/white)	0.05 lux	0.05 lux	0.05 lux
	Night vision	-	-	-
	Max. range at night	-	-	-
Lens	Automatic Back Focus (ABF)	-	-	-
	Automatic varifocal	-	■	■
	Focal length	3 - 10 mm	3 - 10 mm	3 - 10 mm
	Horizontal Angle of View (HAoV)	36° - 117°	36° - 117°	27.8° - 86.6°
DORI distances	Detect/Observe/Recognize/Identify (Distances in m according to EN-50132-7 standard)	24-118/9-47/5-24/2-12	24-118/9-47/5-24/2-12	55-208/22-83/11-42/5-21
Storage	Memory card slot	■ (up to 2 TB)	■ (up to 2 TB)	■ (up to 2 TB)
	Cloud application storage	Auto or Alarm JPEG Posting, Video Clips or JPEG Exporting	Auto or Alarm JPEG Posting, Video Clips or JPEG Exporting	Auto or Alarm JPEG Posting, Video Clips or JPEG Exporting
Connections	Alarm input/output	1/1	1/1	1/1
	Audio in/out	■/■	■/■	■/■
	Hybrid*/confrontation monitor	■/■	■/■	■/■
Housing	Weather rating	-	-	-
	Vandal resistant	-	-	-
	Operating temperature	-20° to 50° C (-4° to 122° F)	-20° to 50° C (-4° to 122° F)	-20° to 50° C (-4° to 122° F)

* The hybrid functionality offers an easy migration path from legacy CCTV to a modern IP-based system

IP Video

Dome Cameras

► FLEXIDOME IP indoor 5000 IR



■ Available – Not available

Commercial Type Number		NII-51022-V3	NII-50022-A3	NII-50051-A3
Bosch USPs	Intelligent Dynamic Noise Reduction (IDNR)	■	■	■
	Intelligent Auto Exposure (IAE)/Intelligent Defog starlight (extreme low-light sensitivity)	- / ■	- / ■	- / ■
	4K ultra HD	-	-	-
	Built-in Intelligent Video Analysis (IVA)	-	-	-
Basic features	Maximum resolution	HD 1080p	HD 1080p	5MP
	Image sensor type	1/2.7"	1/2.7"	1/3"
	Max. frames per second (fps)	30 fps@ 1080p	30 fps@ 1080p	12 fps@ 5MP
	Indoor/outdoor/in-vehicle	■/ - /-	■/ - /-	■/ - /-
	Day/night	■	■	■
	Wide Dynamic Range (WDR)	76dB	76dB	81dB
	ONVIF conformant	■	■	■
	Built-in microphone	■	■	■
	Power over Ethernet (PoE)	■	■	■
Advanced features	Compression (H.264 & MJPEG)/multi-streaming	■/4 streams	■/4 streams	■/4 streams
	Privacy masking	■	■	■
	Region Of Interest tracking	-	-	-
Alarm triggering	Tamper detection	■	■	■
	Video motion detection	■	■	■
	Intelligent Video Analysis (IVA)	-	-	-
	Audio detection	■	■	■
Sensitivity	Minimum illumination day mode (color)	0.24 lux	0.24 lux	0.35 lux
	Minimum illumination night mode (black/white)	0 lux (IR on)	0 lux (IR on)	0 lux (IR on)
	Night vision	■ (infrared)	■ (infrared)	■ (infrared)
	Max. range at night	15 m (50 ft)	15 m (50 ft)	15 m (50 ft)
Lens	Automatic Back Focus (ABF)	-	-	-
	Automatic varifocal	-	■	■
	Focal length	3 - 10 mm	3 - 10 mm	3 - 10 mm
	Horizontal Angle of View (HAoV)	36° - 117°	36° - 117°	27.8° - 86.6°
DORI distances	Detect/Observe/Recognize/Identify (Distances in m according to EN-50132-7 standard)	24-118/9-47/5-24/2-12	24-118/9-47/5-24/2-12	55-208/22-83/11-42/5-21
Storage	Memory card slot	■ (up to 2 TB)	■ (up to 2 TB)	■ (up to 2 TB)
	Cloud application storage	Auto or Alarm JPEG Posting, Video Clips or JPEG Exporting	Auto or Alarm JPEG Posting, Video Clips or JPEG Exporting	Auto or Alarm JPEG Posting, Video Clips or JPEG Exporting
Connections	Alarm input/output	1/1	1/1	1/1
	Audio in/out	■/■	■/■	■/■
	Hybrid*/confrontation monitor	■/■	■/■	■/■
Housing	Weather rating	-	-	-
	Vandal resistant	-	-	-
	Operating temperature	-20° to 50° C (-4° to 122° F)	-20° to 50° C (-4° to 122° F)	-20° to 50° C (-4° to 122° F)

* The hybrid functionality offers an easy migration path from legacy CCTV to a modern IP-based system

IP Video

Dome Cameras

► FLEXIDOME IP outdoor 5000 HD

► FLEXIDOME IP outdoor 5000 IR

► FLEXIDOME IP outdoor 5000 MP

► FLEXIDOME IP outdoor 5000 IR



■ Available – Not available

Commercial Type Number		NDN-50022-A3	NDI-50022-A3	NDN-50051-A3	NDI-50051-A3
Bosch USPs	Intelligent Dynamic Noise Reduction (IDNR)	■	■	■	■
	Intelligent Auto Exposure (IAE)/Intelligent Defog	- / ■	- / ■	- / ■	- / ■
	starlight (extreme low-light sensitivity)	-	-	-	-
	4K ultra HD	-	-	-	-
	Built-in Intelligent Video Analysis (IVA)	-	-	-	-
Basic features	Maximum resolution	HD 1080p	HD 1080p	5MP	5MP
	Image sensor type	1/2.7"	1/2.7"	1/3"	1/3"
	Max. frames per second (fps)	30 fps@ 1080p	30 fps@ 1080p	12 fps@ 5MP	12 fps@ 5MP
	Indoor/outdoor/in-vehicle	■/■/-	■/■/-	■/■/-	■/■/-
	Day/night	■	■	■	■
	Wide Dynamic Range (WDR)	76dB	76dB	81dB	81dB
	ONVIF conformant	■	■	■	■
	Built-in microphone	-	-	-	-
	Power over Ethernet (PoE)	■	■	■	■
	Advanced features	Compression (H.264 & MJPEG)/multi-streaming	■/4 streams	■/4 streams	■/4 streams
Privacy masking		■	■	■	■
Region Of Interest tracking		-	-	-	-
Alarm triggering	Tamper detection	■	■	■	■
	Video motion detection	■	■	■	■
	Intelligent Video Analysis (IVA)	-	-	-	-
	Audio detection	■	■	■	■
Sensitivity	Minimum illumination day mode (color)	0.24 lux	0.24 lux	0.35 lux	0.35 lux
	Minimum illumination night mode (black/white)	0.05 lux	0 lux (IR on)	0.05 lux	0 lux (IR on)
	Night vision	-	■ (infrared)	-	■ (infrared)
	Max. range at night	-	15 m (50 ft)	-	15 m (50 ft)
Lens	Automatic Back Focus (ABF)	-	-	-	-
	Automatic varifocal	■	■	■	■
	Focal length	3 - 10 mm			
	Horizontal Angle of View (HAoV)	36° - 117°	27.8° - 86.6°	36° - 117°	36° - 117°
DORI distances	Detect/Observe/Recognize/Identify (Distances in m according to EN-50132-7 standard)	24-118/9-47/5-24/2-12	24-118/9-47/5-24/2-12	55-208/22-83/11-42/5-21	55-208/22-83/11-42/5-21
Storage	Memory card slot	■ (up to 2 TB)			
	Cloud application storage	Auto or Alarm JPEG Posting, Video Clips or JPEG Exporting	Auto or Alarm JPEG Posting, Video Clips or JPEG Exporting	Auto or Alarm JPEG Posting, Video Clips or JPEG Exporting	Auto or Alarm JPEG Posting, Video Clips or JPEG Exporting
Connections	Alarm input/output	1/1	1/1	1/1	1/1
	Audio in/out	■/■	■/■	■/■	■/■
	Hybrid*/confrontation monitor	■/■	-/■	■/■	■/■
Housing	Weather rating	IP66	IP66	IP66	IP66
	Vandal resistant	IK10	IK10	IK10	IK10
	Operating temperature	-30° to 50° C (-22° to 122° F)	-30° to 50° C (-22° to 122° F)	-30° to 50° C (-22° to 122° F)	-30° to 50° C (-22° to 122° F)

* The hybrid functionality offers an easy migration path from legacy CCTV to a modern IP-based system

IP Video

Dome Cameras

► FLEXIDOME IP starlight 7000 VR



► FLEXIDOME IP 7000 VR



► FLEXIDOME IP dynamic 7000 VR



■ Available – Not available

Commercial Type Number		NIN-733-Vxxxx	NIN-832-Vxxxx	NIN-932-VxxIPx
Bosch USPs	Intelligent Dynamic Noise Reduction (IDNR)	■	■	■
	Intelligent Auto Exposure (IAE)/Intelligent Defog starlight (extreme low-light sensitivity)	■ (IVA models only)/-	■ (IVA models only)/-	■/-
	4K ultra HD	-	-	-
	Built-in Intelligent Video Analysis (IVA)	■ (depends on model/mode)	■ (depends on model/mode)	■
	Basic features			
	Maximum resolution	HD 720p/1.3 MP (4:3)	HD 1080p	HD 1080p
	Image sensor type	1/3"	1/2.7"	1/3"
	Max. frames per second (fps)	60 fps@ 720p	30 fps@ 1080p	30 fps@ 1080p
	Indoor/outdoor/in-vehicle	■/■/-	■/■/-	■/■/-
	Day/night	■	■	■
	Wide Dynamic Range (WDR)	84dB (IVA model with IAE + 16dB)	76dB (IVA model with IAE + 16dB)	90dB (with IAE + 16dB)
	ONVIF conformant	■	■	■
	Built-in microphone	-	-	-
	Power over Ethernet (PoE)	■	■	■
Advanced features	Compression (H.264 & MJPEG)/multi-streaming	■/4 streams	■/4 streams	■/4 streams
	Privacy masking	■	■	■
	Region Of Interest tracking	■	■	■
Alarm triggering	Tamper detection	■	■	■
	Video motion detection	■	■	■
	Intelligent Video Analysis (IVA)	■ (depends on model)	■ (depends on model)	■
	Audio detection	■	■	■
Sensitivity	Minimum illumination day mode (color)	0.017 lux (V03xx) 0.03 lux (V10xx)	0.22 lux (V03xx) 0.4 lux (V10xx)	0.25 lux (V03xx) 0.45 lux (V10xx)
	Minimum illumination night mode (black/white)	0.0057 lux (V03xx) 0.01 lux (V10xx)	0.05 lux (V03xx) 0.1 lux (V10xx)	0.08 lux (V03xx) 0.15 lux (V10xx)
	Night vision	■ (starlight)	-	-
	Max. range at night	-	-	-
	Lens			
	Automatic Back Focus (ABF)	■	■	■
	Automatic varifocal	■	■	■
	Focal length	3 - 9 mm (V03xx) 10 - 23 mm (V10xx)	3 - 9 mm (V03xx) 10 - 23 mm (V10xx)	3 - 9 mm (V03IPx) 10 - 23 mm (V10IPx)
	Horizontal Angle of View (HAoV)	32° - 96° (V03xx) 12.4° - 28° (V10xx)	38° - 121° (V03xx) 14.8° - 34° (V10xx)	28° - 83° (V03IPx) 10.9° - 24° (V10IPx)
DORI distances	Detect/Observe/Recognize/Identify	23-89/9-35/5-18/2-9 (V03xx)	22-112/9-44/4-22/2-11 (V03xx)	43-154/17-61/9-31/4-15 (V03xx)
	(Distances in m according to EN-50132-7 standard)	103-236/41-94/21-47/10-24 (V10xx)	126-296/50-117/25-59/13-30 (V10xx)	181-402/72-160/36-80/18-40 (V10xx)
Storage	Memory card slot	■ (up to 2 TB)	■ (up to 2 TB)	■ (up to 2 TB)
	Cloud application storage	Auto or Alarm JPEG Posting, Face Detection JPEG posting (IVA models only), Video Clips or JPEG Exporting	Auto or Alarm JPEG Posting, Best Face Detection JPEG posting (IVA models only), Video Clips or JPEG Exporting	Auto or Alarm JPEG Posting, Best Face Detection JPEG posting, Video Clips or JPEG Exporting
Connections	Alarm input/output	2/1	2/1	2/1
	Audio in/out	■	■	■
	Hybrid*/confrontation monitor	■/■	■/■	■/■
Housing	Weather rating	IP66	IP66	IP66
	Vandal resistant	IK10	IK10	IK10
	Operating temperature	-30° to 50° C (-22° to 122° F)	-30° to 50° C (-22° to 122° F)	-30° to 50° C (-22° to 122° F)

* The hybrid functionality offers an easy migration path from legacy CCTV to a modern IP-based system

IP Video

Dome Cameras

► FLEXIDOME IP starlight 7000 RD

► FLEXIDOME IP 7000 RD

► FLEXIDOME IP dynamic 7000 RD



■ Available – Not available

Commercial Type Number		NDN-733Vxx-xx	NDN-832Vxx-xx	NDN-932Vxx-IP
Bosch USPs	Intelligent Dynamic Noise Reduction (IDNR)	■	■	■
	Intelligent Auto Exposure (IAE)/Intelligent Defog starlight (extreme low-light sensitivity)	■ (IVA models only)/■	■ (IVA models only)/■	■/■
	4K ultra HD	-	-	-
	Built-in Intelligent Video Analysis (IVA)	■ (depends on model/mode)	■ (depends on model/mode)	■
	Basic features			
	Maximum resolution	HD 720p/1.3 MP (4:3)	HD 1080p	HD 1080p
	Image sensor type	1/3"	1/2.7"	1/3"
	Max. frames per second (fps)	60 fps@ 720p	30 fps@ 1080p	30 fps@ 1080p
	Indoor/outdoor/in-vehicle	■/■/-	■/■/-	■/■/-
	Day/night	■	■	■
	Wide Dynamic Range (WDR)	84dB (IVA model with IAE + 16dB)	76dB (IVA model with IAE + 16dB)	90dB (with IAE + 16dB)
	ONVIF conformant	■	■	■
	Built-in microphone	-	-	-
	Power over Ethernet (PoE)	■	■	■
Advanced features	Compression (H.264 & MJPEG)/multi-streaming	■/4 streams	■/4 streams	■/4 streams
	Privacy masking	■	■	■
	Region Of Interest tracking	■	■	■
Alarm triggering	Tamper detection	■	■	■
	Video motion detection	■	■	■
	Intelligent Video Analysis (IVA)	■ (depends on model)	■ (depends on model)	■
	Audio detection	■	■	■
Sensitivity	Minimum illumination day mode (color)	0.017 lux	0.22 lux	0.25 lux
	Minimum illumination night mode (black/white)	0.0057 lux	0.05 lux	0.08 lux
	Night vision	■ (starlight)	-	-
	Max. range at night	-	-	-
Lens	Automatic Back Focus (ABF)	■	■	■
	Automatic varifocal	-	-	-
	Focal length	1.8 - 3 mm (V02-xx), 3.8 - 13 mm (V03-xx), 9 - 40 mm (V09-xx)	1.8 - 3 mm (V02-xx), 3.8 - 13 mm (V03-xx), 9 - 40 mm (V09-xx)	1.8 - 3 mm (V02-xx), 3.8 - 13 mm (V03-xx), 9 - 40 mm (V09-xx)
	Horizontal Angle of View (HAoV)	77° - 105° (V02-xx), 21° - 72° (V03-xx), 7.1° - 30° (V09-xx)	87° - 115° (V02-xx), 26° - 87° (V03-xx), 8.5° - 37° (V09-xx)	70°-98° (V02-xx), 19°-63° (V03-xx), 6.2°-26° (V09-xx)
DORI distances	Detect/Observe/Recognize/Identify (Distances in m according to EN-50132-7 standard)	20-32/8-13/4-6/2-3 (V02-xx) 35-138/14-55/7-28/4-14 (V03-xx) 96-413/38-164/19-83/10-41 (V09-xx)	16-40/6-16/3-8/2-4 (V02-xx) 27-166/11-66/5-33/3-17 (V03-xx) 77-517/30-205/15-103/8-52 (V09-xx)	22-55/9-22/4-11/2-5 (V02-xx) 42-229/17-91/8-46/4-23 (V03-xx) 111-709/44-281/22-142/11-71 (V09-xx)
	Storage			
	Memory card slot	■ (up to 2 TB)	■ (up to 2 TB)	■ (up to 2 TB)
	Cloud application storage	Auto or Alarm JPEG Posting, Best Face Detection JPEG posting (IVA models only), Video Clips or JPEG Exporting	Auto or Alarm JPEG Posting, Best Face Detection JPEG posting (IVA models only), Video Clips or JPEG Exporting	Auto or Alarm JPEG Posting, Best Face Detection JPEG posting, Video Clips or JPEG Exporting
Connections	Alarm input/output	2/1	2/1	2/1
	Audio in/out	■	■	■
	Hybrid*/confrontation monitor	-/-	-/-	-/-
Housing	Weather rating	IP66 & IP67	IP66 & IP67	IP66 & IP67
	Vandal resistant	Exceeding IK10	Exceeding IK10	Exceeding IK10
	Operating temperature	-50° to 50° C (-58° to 122° F)	-50° to 50° C (-58° to 122° F)	-50° to 50° C (-58° to 122° F)

* The hybrid functionality offers an easy migration path from legacy CCTV to a modern IP-based system

IP Video

Dome Cameras

► FLEXIDOME IP panoramic 5000 MP

► FLEXIDOME IP panoramic 5000 MP

► FLEXIDOME IP panoramic 7000 MP



reddot award 2015
winner



■ Available – Not available

Commercial Type Number		NUC-52051-F0	NUC-52051-F0E	NIN-70122-Fx(A)
Bosch USPs	Intelligent Dynamic Noise Reduction (IDNR)	■	■	■
	Intelligent Auto Exposure (IAE)/Intelligent Defog	-/■	-/■	■ (customized region)/■
	Intelligent Tracking	-	-	■
	Starlight (extreme low-light sensitivity)	-	-	-
	Built-in Intelligent Video Analysis (IVA)	-	-	■ (depends on model)
Basic features	Maximum resolution	5MP	5MP	12MP
	Image sensor type	1/3"	1/3"	1/2.3"
	Max. frames per second (fps)	15 fps	15 fps	30 fps
	Indoor/outdoor/in-vehicle	■/-/-	■/■/-	■/-/-
	Day/night	■ (electronic)	■ (electronic)	■
	Wide Dynamic Range (WDR)	81dB	81dB	92dB (IVA model with IAE + 16dB)
	ONVIF conformant	■	■	■
	Built-in microphone	■	-	■
	Power over Ethernet (PoE)	■	■	■
	Advanced features	Compression (H.264 & MJPEG)/multi-streaming	■/4 streams	■/4 streams
Edge dewarping		-	-	■
Privacy masking		■	■	■
Region Of Interest tracking		-	-	■
Alarm triggering	Tamper detection	■	■	■
	Video motion detection	■	■	■
	Intelligent Video Analysis (IVA)	-	-	■ (depends on model)
	Audio detection	■	-	■
	PTZ Intelligent Tracking	-	-	■
Sensitivity	Minimum illumination day mode (color)	0.36 lux	0.36 lux	0.46 lux (F1) 0.55 lux (F0)
	Minimum illumination night mode (black/white)	0.12 lux	0.12 lux	0.15 lux (F1) 0.18 lux (F0)
	Night vision	-	-	-
	Max. range at night	-	-	-
Lens	Focal length	1.19 mm	1.19 mm	1.6 mm (F1) 2.1 mm (F0)
	Horizontal Angle of View (HAoV)	360°	360°	180° (F1) 360° (F0)
DORI distances	Detect/Observe/Recognize/Identify (Distances in m according to EN-50132-7 standard)	19/7/4/1	19/7/4/1	19/12/6.5/3.5 (F1) 19/8.5/4.5/2 (F0)
Storage	Memory card slot	■ MicroSD (up to 2 TB)	■ MicroSD (up to 2 TB)	■ MicroSD (up to 2 TB)
	Cloud application storage	Auto or Alarm JPEG Posting, Video Clips or JPEG Exporting	Auto or Alarm JPEG Posting, Video Clips or JPEG Exporting	Auto or Alarm JPEG Posting, Best Face Detection JPEG posting (IVA models only), Video Clips or JPEG Exporting
Connections	Alarm input/output	-	-	-
	Audio in/out	-	-	-
	Hybrid*/confrontation monitor	-	-	-
Housing	Weather rating	-	IP66	-
	Vandal resistant	IK4	IK10	IK6
	Operating temperature	-20° C to +50° C (-4° F to 104° F)	-30° C to +50° C (-22° F to 122° F)	-20° C to +40° C (-4° F to 104° F)

* The hybrid functionality offers an easy migration path from legacy CCTV to a modern IP-based system

IP Video

Fixed Cameras

▶TINYON IP 2000



▶TINYON IP 2000 HD



▶TINYON IP 2000 WI



▶TINYON IP 2000 PIR



■ Available – Not available

Commercial Type Number		NPC-20002-F2	NPC-20012-F2L(-W)	NPC-20012-F2WL(-W)	NPC-20012-F2(-W)
Bosch USPs	Intelligent Dynamic Noise Reduction (IDNR)	■	■	■	■
	Intelligent Auto Exposure (IAE)/Intelligent Defog	-/-	-/-	-/-	-/-
	starlight (extreme low-light sensitivity)	-	-	-	-
	4K ultra HD	-	-	-	-
	Built-in Intelligent Video Analysis (IVA)	-	-	-	-
Basic features	Maximum resolution	VGA	HD 720p	HD 720p	HD 720p
	Image sensor type	1/4"	1/4"	1/4"	1/4"
	Max. frames per second (fps)	30 fps@ 480p	30 fps@ 720p	30 fps@ 720p	30 fps@ 720p
	Indoor/outdoor/in-vehicle	■/-/-	■/-/-	■/-/-	■/-/-
	Day/night	■ (electronic)	■ (electronic)	■ (electronic)	■ (electronic)
	Wide Dynamic Range (WDR)	76dB	76dB	76dB	76dB
	ONVIF conformant	■	■	■	■
	Built-in microphone	-	■	■	■
	Power over Ethernet (PoE)	-	■	-	■
	Advanced features	Compression (H.264 & MJPEG)/multi-streaming	■/4 streams	■/4 streams	■/4 streams
Privacy masking		■	■	■	■
Region Of Interest tracking		-	-	-	-
Alarm triggering	Tamper detection	■	■	■	■
	Video motion detection	■	■	■	■
	Intelligent Video Analysis (IVA)	-	-	-	-
	Audio detection	-	■	■	■
	Passive infrared (PIR) motion detection	-	-	■	■
Sensitivity	Minimum illumination day mode (color)	1 lux	1 lux	1 lux 0 lux (with wLED)	1 lux 0 lux (with wLED)
	Minimum illumination night mode (black/white)	-	-	-	-
	Night vision	-	-	■ (wLED)	■ (wLED)
	Max. range at night	-	-	4 m (13 ft)	4 m (13 ft)
Lens	Automatic Back Focus (ABF)	-	-	-	-
	Automatic varifocal	-	-	-	-
	Focal length	2.5 mm	2.5 mm	2.5 mm	2.5 mm
	Horizontal Angle of View (HAoV)	75°	89°	89°	89°
DORI distances	Detect/Observe/Recognize/Identify (Distances in m according to EN-50132-7 standard)	16/7/3/2	26/10/5/3	26/10/5/3	26/10/5/3
Storage	Memory card slot	■ (up to 2 TB)	■ (up to 2 TB)	-	■ (up to 2 TB)
	Cloud application storage	Auto or Alarm JPEG Posting, Video Clips or JPEG Exporting	Auto or Alarm JPEG Posting, Video Clips or JPEG Exporting	Auto or Alarm JPEG Posting, Video Clips or JPEG Exporting	Auto or Alarm JPEG Posting, Video Clips or JPEG Exporting
Connections	Alarm input/output	-/-	-/-	■/■	■/■
	Audio in/out	-/-	-/- (built-in loudspeaker)	-/- (built-in loudspeaker)	-/- (built-in loudspeaker)
	Hybrid*/confrontation monitor	-/-	-/-	-/-	-/-
	Wireless (WPS, IEEE 802, 11b/g/n)	-	-	■	-
Housing	Weather rating	-	-	-	-
	Vandal resistant	-	-	-	-
	Operating temperature	-10° to 45° C (14° to 113° F)	-10° to 50° C (14° to 122° F)	-10° to 40° C (14° to 104° F)	-10° to 45° C (14° to 113° F)

* The hybrid functionality offers an easy migration path from legacy CCTV to a modern IP-based system

IP Video

Fixed Cameras



■ Available – Not available

Commercial Type Number		NBN-40012-xxx	NBN-50022-xxx	NBN-50051-xxx	NTI-40012-A3(S)**	NTI-50022-A3(S)**
Bosch USPs	Intelligent Dynamic Noise Reduction (IDNR)	■	■	■	■	■
	Intelligent Auto Exposure (IAE)/Intelligent Defog starlight (extreme low-light sensitivity)	-/■	-/■	-/-	-/■	-/■
	4K ultra HD	-	-	-	-	-
	Built-in Intelligent Video Analysis (IVA)	-	-	-	-	-
	Basic features					
	Maximum resolution	HD 720p/1.3 MP (4:3)	HD 1080p	5MP	HD 720p	HD 1080p
	Image sensor type	1/2.7"	1/2.7"	1/3"	1/2.9"	1/2.9"
	Max. frames per second (fps)	30 fps@ 720p	30 fps@ 1080p	12 fps@ 5MP	30 fps@ 720p	30 fps@ 1080p
	Indoor/outdoor/in-vehicle	■/■ (with housing)/-	■/■ (with housing)/-	■/■ (with housing)/-	■/■/-	■/■/-
	Day/night	■	■	■	■	■
	Wide Dynamic Range (WDR)	76dB	76dB	81dB	76dB	76dB
	ONVIF conformant	■	■	■	■	■
	Built-in microphone	■	■	■	-	-
	Power over Ethernet (PoE)	■	■	■	■	■
Advanced features	Compression (H.264 & MJPEG)/multi-streaming	■/4 streams				
	Privacy masking	■	■	■	■	■
	Region Of Interest tracking	-	-	-	-	-
Alarm triggering	Tamper detection	■	■	■	■	■
	Video motion detection	■	■	■	■	■
	Intelligent Video Analysis (IVA)	-	-	-	-	-
	Audio detection	■	■	■	■	■
Sensitivity	Minimum illumination day mode (color)	0.25 lux	0.25 lux	0.35 lux	0.07 lux	0.07 lux
	Minimum illumination night mode (black/white)	0.05 lux	0.05 lux	0.05 lux	0 lux (IR on)	0 lux (IR on)
	Night vision	-	-	-	■ (infrared)	■ (infrared)
	Max. range at night	-	-	-	30 m (98 ft)	30 m (98 ft)
Lens	Automatic Back Focus (ABF)	-	-	-	-	-
	Automatic varifocal	-	-	-	■	■
	Focal length	3.3 - 12 mm (V3)/CS mount	3.3 - 12 mm (V3)/CS mount	3.3 - 12 mm (V3)/CS mount	2.7 - 12 mm	2.7 - 12 mm
	Horizontal Angle of View (HAoV)	34° - 110° (V3)	34° - 110° (V3)	25° - 82° (V3)	32° - 100°	32° - 100°
DORI distances	Detect/Observe/Recognize/Identify (Distances in m according to EN-50132-7 standard)	18-84/7-33/4-17/2-8 (V3)	27-125/11-50/5-25/3-13 (V3)	60-234/24-93/12-47/6-23 (V3)	21-89/8-35/4-17/2-9	21-89/8-35/4-17/2-9
	Storage					
	Memory card slot	■ (up to 2 TB)				
	Cloud application storage	Auto or Alarm JPEG Posting, Video Clips or JPEG Exporting	Auto or Alarm JPEG Posting, Video Clips or JPEG Exporting	Auto or Alarm JPEG Posting, Video Clips or JPEG Exporting	Auto or Alarm JPEG Posting, Video Clips or JPEG Exporting	Auto or Alarm JPEG Posting, Video Clips or JPEG Exporting
Connections	Alarm input/output	1/1	1/1	1/1	1/1	1/1
	Audio in/out	■/■	■/■	■/■	■/■	■/■
	Hybrid*/confrontation monitor	■/■	■/■	■/■	■/■	■/■
Housing	Weather rating	-	-	-	IP66	IP66
	Vandal resistant	-	-	-	IK08	IK08
	Operating temperature	-30° to 50° C (-22° to 122° F)	-30° to 50° C (-22° to 122° F)	-30° to 50° C (-22° to 122° F)	-30° to 60° C (-22° to 140° F)	-30° to 60° C (-22° to 140° F)

* The hybrid functionality offers an easy migration path from legacy CCTV to a modern IP-based system

** The NTI-40012-A3S model has a pre-mounted Surface Mount Box

IP Video

Fixed Cameras

►DINION IP starlight 7000 HD



►DINION IP 7000 HD



►DINION IP dynamic 7000 HD



■ Available – Not available

Commercial Type Number		NBN-71013-xx**/NKN-71013-BAx-xxN***	NBN-71022-xx**/NKN-71022-BAx-xxN***	NBN-71027-xx**/NKN-71027-BAx-xxN***
Bosch USPs	Intelligent Dynamic Noise Reduction (IDNR)	■	■	■
	Intelligent Auto Exposure (IAE)/Intelligent Defog	■/■	■/■	■/■
	starlight (extreme low-light sensitivity)	■	-	-
	4K ultra HD	-	-	-
	Built-in Intelligent Video Analysis (IVA)	■ (depends on model/mode)	■ (depends on model/mode)	■
Basic features	Maximum resolution	HD 720p/1.3 MP (4:3)	HD 1080p	HD 1080p
	Image sensor type	1/3"	1/2.7"	1/3"
	Max. frames per second (fps)	60 fps@ 720p	30 fps@ 1080p	30 fps@ 1080p
	Indoor/outdoor/in-vehicle	■/■ (with housing)/-	■/■ (with housing)/-	■/■ (with housing)/-
	Day/night	■	■	■
	Wide Dynamic Range (WDR)	84dB (IVA model with IAE + 16dB)	76dB (IVA model with IAE + 16dB)	90dB (with IAE + 16dB)
	ONVIF conformant	■	■	■
	Built-in microphone	-	-	-
	Power over Ethernet (PoE)	■	■	■
	Advanced features	Compression (H.264 & MJPEG)/multi-streaming	■/4 streams	■/4 streams
	Privacy masking	■	■	■
	Region Of Interest tracking	■	■	■
Alarm triggering	Tamper detection	■	■	■
	Video motion detection	■	■	■
	Intelligent Video Analysis (IVA)	■ (depends on model)	■ (depends on model)	■
	Audio detection	■	■	■
Sensitivity	Minimum illumination day mode (color)	0.017 lux	0.22 lux	0.25 lux
	Minimum illumination night mode (black/white)	0.0057 lux	0.05 lux	0.08 lux
	Night vision	■ (starlight)	-	-
	Max. range at night	-	-	-
Lens	Automatic Back Focus (ABF)	■	■	■
	Automatic varifocal	-	-	-
	Focal length	C/CS mount (NBN), 9 - 40 mm (NKN-71013-BA4), 3.8 - 13 mm (NKN-71013-BA3)	C/CS mount (NBN), 9 - 40 mm (NKN-71022-BA4), 3.8 - 13 mm (NKN-71022-BA3)	C/CS mount (NBN), 9 - 40 mm (NKN-71027-BA4), 3.8 - 13 mm (NKN-71027-BA3)
	Horizontal Angle of View (HAoV)	depending on optional lens	depending on optional lens	depending on optional lens
DORI distances	Detect/Observe/Recognize/Identify (Distances in m according to EN-50132-7 standard)	depending on optional lens	depending on optional lens	depending on optional lens
	Storage	Memory card slot	■ (up to 2 TB)	■ (up to 2 TB)
	Cloud application storage	Auto or Alarm JPEG Posting, Best Face Detection JPEG posting (IVA models only), Video Clips or JPEG Exporting	Auto or Alarm JPEG Posting, Best Face Detection JPEG posting (IVA models only), Video Clips or JPEG Exporting	Auto or Alarm JPEG Posting, Best Face Detection JPEG posting (IVA models only), Video Clips or JPEG Exporting
Connections	Alarm input/output	2/1	2/1	2/1
	Audio in/out	■/■	■/■	■/■
	Hybrid*/confrontation monitor	■/■	■/■	■/■
Housing	Weather rating	IP66 (NKN models only)	IP66 (NKN models only)	IP66 (NKN models only)
	Vandal resistant	-	-	-
	Operating temperature	-20° to 50° C (-4° to 122° F)	-20° to 55° C (-4° to 131° F)	-20° to 50° C (-4° to 122° F)

* The hybrid functionality offers an easy migration path from legacy CCTV to a modern IP-based system

** Lens not included

*** Ready-to-go, factory assembled pre-packaged camera kits include: DINION IP 7000 camera, lens, indoor/outdoor housing, assembled, pre-wired and back-focussed. EMEA region models: NKN-71013-BAx-10N. US region models: NKN-71013-BAx-20N

IP Video
Fixed Cameras

►DINION IP starlight 8000 MP



►DINION IP ultra 8000 MP



■ Available – Not available

Commercial Type Number		NBN-80052-BA	NBN-80122-xxx
Bosch USPs	Intelligent Dynamic Noise Reduction (IDNR)	■	■
	Intelligent Auto Exposure (IAE)/Intelligent Defog starlight (extreme low-light sensitivity)	■/-	■/-
	4K ultra HD	-	-
	Built-in Intelligent Video Analysis (IVA)	■	■
	Basic features		
	Maximum resolution	5 MP (16:9)/5.5 MP (4:3)	12 MP (4:3)/UHD (16:9)
	Image sensor type	1/1.8"	1/2.3"
	Max. frames per second (fps)	30 fps@ 5 MP	20 fps@ 12MP, 30 fps@ UHD
	Indoor/outdoor/in-vehicle	■/■ (with housing)/-	■/■ (with housing)/-
	Day/night	■	■
	Wide Dynamic Range (WDR)	97dB (5MP)/105dB (1080p) (with IAE + 16dB)	92dB (with IAE + 16dB)
	ONVIF conformant	■	■
	Built-in microphone	-	-
	Power over Ethernet (PoE)	■	■
Advanced features	Compression (H.264 & MJPEG)/multi-streaming	■/4 streams	■/4 streams
	Privacy masking	■	■
	Region Of Interest tracking	■	■
Alarm triggering	Tamper detection	■	■
	Video motion detection	■	■
	Intelligent Video Analysis (IVA)	■	■
	Audio detection	■	■
Sensitivity	Minimum illumination day mode (color)	0.0121 lux (5 MP) 0.00825 lux (1080p)	0.36 lux (FxA) 0.11 lux (CA)
	Minimum illumination night mode (black/white)	0.004 lux (5 MP) 0.00275 lux (1080p)	0.12 lux (FxA) 0.037 lux (CA)
	Night vision	■ (starlight)	-
	Max. range at night	-	-
	Lens	Automatic Back Focus (ABF)	■
	Automatic varifocal	-	-
	Focal length	C/CS mount	3.2 mm (F2A) 5 mm (F6A) C/CS mount (CA) - 35/50/75
	Horizontal Angle of View (HAoV)	Depending on optional lens	71° (F6A) 120° (F2A) C/CS mount (CA) - 35/50/75
DORI distances	Detect/Observe/Recognize/Identify (Distances in m according to EN-50132-7 standard)	Depending on optional lens	46/18/9/5 (F2A) 114/45/23/11 (F6A) Depending on optional lens (CA)
	Storage		
	Memory card slot	■ (up to 2 TB)	■ (up to 2 TB)
	Cloud application storage	Auto or Alarm JPEG Posting, Best Face Detection JPEG posting (IVA models only), Video Clips or JPEG Exporting	Auto or Alarm JPEG Posting, Best Face Detection JPEG posting (IVA models only), Video Clips or JPEG Exporting
Connections	Alarm input/output	2/1	2/1
	Audio in/out	■/■	■/■
	Hybrid*/confrontation monitor	■/■	-/-
Housing	Weather rating	-	-
	Vandal resistant	-	-
	Operating temperature	-20° to 50° C (-4° to 122° F)	-20° to 50° C (-4° to 122° F)

* The hybrid functionality offers an easy migration path from legacy CCTV to a modern IP-based system

IP Video Specialty Cameras

►DINION IP capture 5000



►DINION IP imager 9000 HD



►FLEXIDOME IP corner 9000 MP



■ Available – Not available

Commercial Type Number		NER-L2Rx-1	NAI-90022-AAA	NCN-90022-F1
Bosch USPs	Intelligent Dynamic Noise Reduction (IDNR)	-	■	■
	Intelligent Auto Exposure (IAE)/Intelligent Defog	-/-	■/-	-/-
	starlight (extreme low-light sensitivity)	-	-	-
	4K ultra HD	-	-	-
	Built-in Intelligent Video Analysis (IVA)	-	■	-
Basic features	Maximum resolution	576p	HD 1080p	1080p
	Image sensor type	1/3"	1/2.7"	1/2.7"
	Max. frames per second (fps)	30 fps@ 576p	30 fps@ 1080p	30 fps@ 1080p
	Indoor/outdoor/in-vehicle	-/■/-	-/■/-	■/-/-
	Day/night	■	■	■
	Wide Dynamic Range (WDR)	120dB	76dB (with IAE +16dB)	76dB
	ONVIF conformant	■	■	■
	Built-in microphone	-	-	-
	Power over Ethernet (PoE)	■	■ (HiPoE)	■
Advanced features	Compression (H.264 & MJPEG)/multi-streaming	■/4 streams	■/4 streams	■/4 streams
	Privacy masking	-	■	■
	Region Of Interest tracking	-	■	-
Alarm triggering	Tamper detection	■	■	■
	Video motion detection	■	■	■
	Intelligent Video Analysis (IVA)	-	■	-
	Audio detection	-	■	■
Sensitivity	Minimum illumination day mode (color)	-	0.4 lux	0.3 lux
	Minimum illumination night mode (black/white)	0 lux (IR on)	0 lux (IR on)	0 lux (IR on)
	Night vision	■ (infrared)	■ (infrared)	■ (infrared)
	Max. range at night	28 m (92 ft)	120 m (394 ft)	9 m (30 ft)
Lens	Automatic Back Focus (ABF)	-	■	-
	Automatic varifocal	-	■	-
	Focal length	5 - 50 mm varifocal (calibrated to optimal capture distance)	10 - 23 mm	2 mm
	Horizontal Angle of View (H AoV)	5.3° - 31.9°	14.8° - 34°	121°
DORI distances	Detect/Observe/Recognize/Identify (Distances in m according to EN-50132-7 standard)	-	126-296/50-117/25-59/13-30	20/8/4/2
	Memory card slot	■ (up to 2 TB)	■ (up to 2 TB)	■ (up to 2 TB)
Storage	Cloud application storage	Auto or Alarm JPEG Posting, Video Clips or JPEG Exporting	Auto or Alarm JPEG Posting, Best Face Detection JPEG posting, Video Clips or JPEG Exporting	Auto or Alarm JPEG Posting, Video Clips or JPEG Exporting
	Connections	Alarm input/output	-/-	1/1
Housing	Audio in/out	-/-	■/■	■/■
	Hybrid*/confrontation monitor	-/-	■/■	-/-
	Weather rating	IP67	IP66	IP65
	Vandal resistant	-	IK10	IK10
	Operating temperature	-40° to 50° C (-40° to 122° F)	-40° to 50° C (-40° to 122° F)	-10° to 50° C (14° to 122° F)

* The hybrid functionality offers an easy migration path from legacy CCTV to a modern IP-based system

IP Video Specialty Cameras

►EXTEGRA IP starlight 9000 FX



►EXTEGRA IP dynamic 9000 FX



►VOT thermal



■ Available – Not available

Commercial Type Number		NXF-9130-xx	NXF-9230-xx	VOT-320-Vxxx
Bosch USPs	Intelligent Dynamic Noise Reduction (IDNR)	■	■	-
	Intelligent Auto Exposure (IAE)/Intelligent Defog starlight (extreme low-light sensitivity)	- /-	- /-	- /-
	4K ultra HD	-	-	-
	Built-in Intelligent Video Analysis (IVA)	■	■	■
	Basic features			
	Maximum resolution	HD 720p	HD 1080p	320 x 240
	Image sensor type	1/3"	1/2.8"	FPA - Vox
	Max. frames per second (fps)	60 fps@ 720p	30 fps@ 1080p	8.3 fps@ 240p (-VxxL), 30 fps@ 240p (-VxxH)
	Indoor/outdoor/in-vehicle	-/■ (ex-proof/corrosive)/-	-/■ (ex-proof/corrosive)/-	■/■/-
	Day/night	■	■	-
	Wide Dynamic Range (WDR)	90dB	90dB	-
	ONVIF conformant	■	■	■
	Built-in microphone	-	-	-
	Power over Ethernet (PoE)	■ (HiPoE)	■ (HiPoE)	-
Advanced features	Compression (H.264 & MJPEG)/multi-streaming	■	■	■/4 streams
	Privacy masking	■	■	-
	Region Of Interest tracking	-	-	-
Alarm triggering	Tamper detection	■	■	■
	Video motion detection	■	■	■
	Intelligent Video Analysis (IVA)	■	■	■
	Audio detection	■	■	■
Sensitivity	Minimum illumination day mode (color)	0.052 lux	0.066 lux	-
	Minimum illumination night mode (black/white)	0.0103 lux	0.033 lux	0 lux
	Night vision	■ (external EX65 IR)	■ (external EX65 IR)	■ (thermal)
	Max. range at night	-	-	1450 m (4758 ft)
Lens	Automatic Back Focus (ABF)	■	■	-
	Automatic varifocal	■	■	-
	Focal length	4.3 - 129 mm	4.3 - 129 mm	9 mm (-V9L, -V9H), 13 mm (-V13L, -V13H), 19 mm (-V19L, -V19H), 60 mm (-V60L, -V60H)
	Horizontal Angle of View (HAoV)	2.1° to 59°	2.1° to 59°	-
DORI distances	Detect/Observe/Recognize/Identify (Distances in m according to EN-50132-7 standard)	45-1397/18-554/9-279/5-140	68-2095/27-831/14-419/7-210	Depending on optional lens
Storage	Memory card slot	■ (up to 2 TB)	■ (up to 2 TB)	■ (up to 32 GB)
	Cloud application storage	Auto or Alarm JPEG Posting (FTP only)	Auto or Alarm JPEG Posting (FTP only)	Auto or Alarm JPEG Posting (FTP only)
Connections	Alarm input/output	3/2	3/2	2/2
	Audio in/out	1/1	1/1	- /-
	Hybrid*/confrontation monitor	- /-	- /-	- /-
Housing	Weather rating	IP67	IP67	IP66
	Vandal resistant	-	-	-
	Operating temperature	-50° to 60° C (-58° to 140° F) (aluminum) -50° to 55° C (-58° to 131° F) (stainless steel)	-50° to 60° C (-58° to 140° F) (aluminum) -50° to 55° C (-58° to 131° F) (stainless steel)	-50° to 55° C (-58° to 131° F)

* The hybrid functionality offers an easy migration path from legacy CCTV to a modern IP-based system

IP Video

Moving Cameras

▶AUTODOME IP 4000 HD



▶AUTODOME IP 4000 HD



■ Available – Not available

Commercial Type Number		NEZ-4112-XXXW4	NEZ-4212-XXXW4
Bosch USPs	Intelligent Dynamic Noise Reduction (IDNR)	■	■
	Intelligent Auto Exposure (IAE)/Intelligent Defog	-/■	-/■
	Intelligent Tracking	-	-
	starlight (extreme low-light sensitivity)	-	-
	Built-in Intelligent Video Analysis (IVA)	-	-
Basic features	Maximum resolution	HD 720p	HD 1080p
	Image sensor type	1/2.8" CMOS	1/2.8" CMOS
	Max. frames per second (fps)	30 fps@ 720p	30 fps@ 1080p
	Indoor/outdoor/in-vehicle	■/-/-	■/-/-
	Day/night	■	■
	Wide Dynamic Range (WDR)	76dB	76dB
	ONVIF conformant	■	■
	Built-in microphone	-	-
	Power over Ethernet (PoE)	■ (PoE+)	■ (PoE+)
	Advanced features	Compression (H.264 & MJPEG)/multi-streaming	■/4 streams
Privacy masking		■	■
Nbr of presets/guard tours		256/2	256/2
Wiper		-	-
Alarm triggering	Tamper detection	-	-
	Video motion detection	■	■
	Intelligent Video Analysis (IVA)	-	-
	Audio detection	-	-
	PTZ Intelligent Tracking	-	-
Sensitivity	Minimum illumination day mode (color)	0.17 lux	0.17 lux
	Minimum illumination night mode (black/white)	0.039 lux	0.039 lux
	Night vision	-	-
	Max. range at night	-	-
Lens	Focal length	5.1 ~ 61.2 mm	5.1 ~ 61.2 mm
	Horizontal Angle of View (H AoV)	4.64° to 51.3°	4.64° to 51.3°
	PTZ Zoom optical/digital	12x/16x	12x/16x
	Tilt angle	-90° to 0°	-90° to 0°
	DORI distances	Detect/Observe/Recognize/Identify (Distances in m according to EN-50132-7 standard)	53-632/21-251/11-126/5-63
Storage	Memory card slot	■ (up to 2 TB)	■ (up to 2 TB)
	Cloud application storage	Auto or Alarm JPEG Posting, Video Clips or JPEG Exporting	Auto or Alarm JPEG Posting, Video Clips or JPEG Exporting
Connections	Alarm input/output	2/1	2/1
	Audio in/out	■/■	■/■
	Hybrid*/confrontation monitor	-/-	-/-
Housing	Weather rating	IP65 (pendant)/IP51 (in-ceiling)	IP65 (pendant)/IP51 (in-ceiling)
	Vandal resistant	IK10	IK10
	Operating temperature	-10° to 60° C (-14° to 140° F)	-10° to 60° C (-14° to 140° F)

* The hybrid functionality offers an easy migration path from legacy CCTV to a modern IP-based system

IP Video

Moving Cameras

▶AUTODOME IP 5000 HD ▶AUTODOME IP 5000 HD ▶AUTODOME IP 5000 IR ▶AUTODOME IP 5000 IR



■ Available – Not available

Commercial Type Number		NEZ 5130-XXXW4	NEZ 5230-XXXW4	NEZ 5130-IRCW4	NEZ 5230-IRCW4
Bosch USPs	Intelligent Dynamic Noise Reduction (IDNR)	■	■	■	■
	Intelligent Auto Exposure (IAE)/Intelligent Defog	-/■	-/■	-/■	-/■
	Intelligent Tracking	-	-	-	-
	starlight (extreme low-light sensitivity)	-	-	-	-
	Built-in Intelligent Video Analysis (IVA)	-	-	-	-
Basic features	Maximum resolution	HD 720p	HD 1080p	HD 720p	HD 1080p
	Image sensor type	1/2.8" CMOS	1/2.8" CMOS	1/2.8" CMOS	1/2.8" CMOS
	Max. frames per second (fps)	30 fps@ 720p	30 fps@ 1080p	30 fps@ 720p	30 fps@ 1080p
	Indoor/outdoor/in-vehicle	■/■/-	■/■/-	-/■/-	-/■/-
	Day/night	■	■	■	■
	Wide Dynamic Range (WDR)	76dB	76dB	76dB	76dB
	ONVIF conformant	■	■	■	■
	Built-in microphone	-	-	-	-
	Power over Ethernet (PoE)	■ (PoE+)	■ (PoE+)	■ (PoE+)	■ (PoE+)
	Advanced features	Compression (H.264 & MJPEG)/multi-streaming	■/4 streams	■/4 streams	■/4 streams
Privacy masking	■	■	■	■	
Nbr of presets/guard tours	256/2	256/2	256/2	256/2	
Wiper	-	-	-	-	
Alarm triggering	Tamper detection	-	-	-	-
	Video motion detection	■	■	■	■
	Intelligent Video Analysis (IVA)	-	-	-	-
	Audio detection	-	-	-	-
	PTZ Intelligent Tracking	-	-	-	-
Sensitivity	Minimum illumination day mode (color)	0.22 lux	0.22 lux	0.11 lux	0.11 lux
	Minimum illumination night mode (black/white)	0.044 lux	0.044 lux	0 lux (IR on)	0 lux (IR on)
	Night vision	-	-	■ (infrared)	■ (infrared)
	Max. range at night	-	-	180 m (590 ft)	180 m (590 ft)
Lens	Focal length	4.3 ~ 129 mm	4.3 ~ 129 mm	4.3 ~ 129 mm	4.3 ~ 129 mm
	Horizontal Angle of View (HAoV)	2.3° to 65°	2.3° to 65°	2.3° to 65°	2.3° to 65°
	PTZ Zoom optical/digital	30x/16x	30x/16x	30x/16x	30x/16x
	Tilt angle	-90° to 0°	-90° to 0°	-90° to 0°	-90° to 0°
	DORI distances	Detect/Observe/Recognize/Identify (Distances in m according to EN-50132-7 standard)	40-1275/16-506/8-255/4-128	60-1913/24-759/12-383/6-191	40-1275/16-506/8-255/4-128
Storage	Memory card slot	■ (up to 2 TB)	■ (up to 2 TB)	■ (up to 2 TB)	■ (up to 2 TB)
	Cloud application storage	Auto or Alarm JPEG Posting, Video Clips or JPEG Exporting	Auto or Alarm JPEG Posting, Video Clips or JPEG Exporting	Auto or Alarm JPEG Posting, Video Clips or JPEG Exporting	Auto or Alarm JPEG Posting, Video Clips or JPEG Exporting
Connections	Alarm input/output	2/1	2/1	2/1	2/1
	Audio in/out	■/■	■/■	■/■	■/■
	Hybrid*/confrontation monitor	-/-	-/-	-/-	-/-
Housing	Weather rating	IP66 (pendant)/IP51 (in-ceiling)	IP66 (pendant)/IP51 (in-ceiling)	IP66	IP66
	Vandal resistant	IK10	IK10	-	-
	Operating temperature	-40° to 60° C (-40° to 140° F)	-40° to 60° C (-40° to 140° F)	-40° to 60° C (-40° to 140° F)	-40° to 60° C (-40° to 140° F)

* The hybrid functionality offers an easy migration path from legacy CCTV to a modern IP-based system

IP Video

Moving Cameras

▶AUTODOME IP 7000



▶AUTODOME IP 7000 HD



▶AUTODOME IP starlight 7000 HD



▶AUTODOME IP dynamic 7000 HD



■ Available – Not available

Commercial Type Number		VG5-7028/7036	VG5-7220	VG5-7130	VG5-7230
Bosch USPs	Intelligent Dynamic Noise Reduction (IDNR)	–	–	■	■
	Intelligent Auto Exposure (IAE)/Intelligent Defog	–/–	–/–	–/■	–/■
	Intelligent Tracking	■	■	■	■
	starlight (extreme low-light sensitivity)	–	–	■	–
	Built-in Intelligent Video Analysis (IVA)	■	■	■	■
Basic features	Maximum resolution	4CIF	HD 1080p	HD 720p	HD 1080p
	Image sensor type	1/4" CCD	1/2.8"	1/3" CMOS	1/2.8"
	Max. frames per second (fps)	30 fps@ 576p	60 fps@ 720p 30 fps@ 1080p	60 fps@ 720p	60 fps@ 720p 30 fps@ 1080p
	Indoor/outdoor/in-vehicle	■/■/–	■/■/–	■/■/–	■/■/–
	Day/night	■	■	■	■
	Wide Dynamic Range (WDR)	92dB	86dB	90dB	90dB
	ONVIF conformant	■	■	■	■
	Built-in microphone	–	–	–	–
	Power over Ethernet (PoE)	■ (HiPoE)	■ (HiPoE)	■ (HiPoE)	■ (HiPoE)
	Advanced features	Compression (H.264 & MJPEG)/multi-streaming	■/4 streams	■/4 streams	■/4 streams
Privacy masking		■	■	■	■
Nbr of presets/guard tours		256/2	256/2	256/2	256/2
Wiper		–	–	–	–
Alarm triggering	Tamper detection	■	■	■	■
	Video motion detection	■	■	■	■
	Intelligent Video Analysis (IVA)	■	■	■	■
	Audio detection	■	■	■	■
	PTZ Intelligent Tracking	■	■	■	■
Sensitivity	Minimum illumination day mode (color)	0.66 lux (36x) 0.33 lux (28x)	0.8 lux	0.052 lux	0.066 lux
	Minimum illumination night mode (black/white)	0.104 lux (36x) 0.066 lux (28x)	0.12 lux	0.0103 lux	0.033 lux
	Night vision	–	–	■ (starlight)	–
	Max. range at night	–	–	–	–
Lens	Focal length	3.4 - 122.4 mm (x36) 3.5 - 98 mm (x28)	4.7 - 94 mm	4.3 - 129 mm	4.3 - 129 mm
	Horizontal Angle of View (HAoV)	28x : 2.13 to 54.98 36x : 1.7 to 56.35	2.9 to 54.1	2.3° to 59°	2.3° to 65°
	PTZ Zoom optical/digital	36x or 28x/12x	20x/12x	30x/12x	30x/12x
	Tilt angle	-90° to 14° (pendant)	-90° to 14° (pendant)	-90° to 14° (pendant)	-90° to 14° (pendant)
	DORI distances	Detect/Observe/Recognize/Identify (Distances in m according to EN-50132-7 standard)	27-757/11-301/5-151/3-76 (28x) 26-949/10-377/5-190/3-95 (36x)	75-1517/30-602/15-303/8-152	45-1275/18-506/9-255/5-128
Storage	Memory card slot	■ (up to 32 GB/2 TB)	■ (up to 32 GB/2 TB)	■ (up to 2 TB)	■ (up to 2 TB)
	Cloud application storage	Auto or Alarm JPEG Posting, Video Clips or JPEG Exporting	Auto or Alarm JPEG Posting, Video Clips or JPEG Exporting	Auto or Alarm JPEG Posting, Video Clips or JPEG Exporting	Auto or Alarm JPEG Posting, Video Clips or JPEG Exporting
Connections	Alarm input/output	7/4	7/4	7/4	7/4
	Audio in/out	■/■	■/■	■/■	■/■
	Hybrid*/confrontation monitor	–/–	–/–	–/–	–/–
Housing	Weather rating	IP66 (outdoor)	IP66 (outdoor)	IP66 (outdoor)	IP66 (outdoor)
	Vandal resistant	IK08 (with rugged bubble)	–	–	–
	Operating temperature	-40° to 55° C (-40° F to 131° F)	-40° to 55° C (-40° F to 131° F)	-40° to 55° C (-40° F to 131° F)	-40° to 55° C (-40° F to 131° F)

* The hybrid functionality offers an easy migration path from legacy CCTV to a modern IP-based system

IP Video

Moving Cameras

►MIC IP starlight 7000 HD



►MIC IP dynamic 7000 HD



►MIC 612



■ Available – Not available

Commercial Type Number		MIC-7130-Px4xx	MIC-7230-Px4xx	MIC612 **
Bosch USPs	Intelligent Dynamic Noise Reduction (IDNR)	■	■	-
	Intelligent Auto Exposure (IAE)/Intelligent Defog	-/■	-/■	-/-
	Intelligent Tracking	■	■	-
	starlight (extreme low-light sensitivity)	■	-	-
	Built-in Intelligent Video Analysis (IVA)	■	■	■
Basic features	Maximum resolution	HD 720p	HD 1080p	550 TVL (optical) 320/640 (thermal)
	Image sensor type	1/3"	1/2.8"	1/4" CCD/FPA
	Max. frames per second (fps)	60 fps@ 720p	30 fps@ 1080p	30 fps@ 576p
	Indoor/outdoor/in-vehicle	-/■/-	-/■/-	-/■/-
	Day/night	■	■	■ (optical)
	Wide Dynamic Range (WDR)	90dB	90dB	-
	ONVIF conformant	■	■	■
	Power over Ethernet (PoE)	■ (HiPoE)	■ (HiPoE)	-
Advanced features	Compression (H.264 & MJPEG)/multi-streaming	■/4 streams	■/4 streams	■/4 streams
	Privacy masking	■	■	■
	Nbr of presets/guard tours	256/2	256/2	99/2
	Wiper	■	■	■
Alarm triggering	Tamper detection	■	■	■
	Video motion detection	■	■	■
	Intelligent Video Analysis (IVA)	■	■	■
	Audio detection	■ (with VJC-7000-90)	■ (with VJC-7000-90)	-
	PTZ Intelligent Tracking	■	■	-
Sensitivity	Minimum illumination day mode (color)	0.052 lux	0.066 lux	0.66 lux (optical) N.A. (thermal)
	Minimum illumination night mode (black/white)	0.0103 lux	0.033 lux	0.104 lux (optical) 0 lux (thermal)
	Night vision	■ (optional illuminator)	■ (optional illuminator)	■ (thermal)
	Max. range at night	175 m (575 ft)	150 m (490 ft)	1500 m (4922 ft)
Lens	Focal length	4.3 - 129 mm	4.3 - 129 mm	3.4 - 122.4 mm (optical), 35 mm (thermal T models) 50 mm (thermal H models)
	Horizontal Angle of View (HAoV)	2.1° to 59°	2.3° to 65°	1.7° to 57.8°
	PTZ Zoom optical/digital	30x/12x	30x/12x	36x/12x
	Tilt angle	-58° to 90° (upright), -90° to 90° (canted)	-58° to 90° (upright), -90° to 90° (canted)	-58° to 90°
DORI distances	Detect/Observe/Recognize/Identify (Distances in m according to EN-50132-7 standard)	45-1397/18-554/9-279/5-140	60-2095/24-831/12-419/6-210	26-949/10-377/5-190/3-95 (optical)
Storage	Memory card slot	■ (up to 32 GB) (with VJC-7000-90)	■ (up to 32 GB) (with VJC-7000-90)	■ (up to 32 GB)
	Cloud application storage	Auto or Alarm JPEG Posting, Video Clips or JPEG Exporting	Auto or Alarm JPEG Posting, Video Clips or JPEG Exporting	Auto or Alarm JPEG Posting, Video Clips or JPEG Exporting
Connections	Alarm input/output	5/3 (with MIC-ALM-WAS-24)	5/3 (with MIC-ALM-WAS-24)	8/2 (optional card)
	Audio in/out	■/■ (with VJC-7000-90)	■/■ (with VJC-7000-90)	■/■
	Hybrid*/confrontation monitor	■ (with external decoder)/-	■ (with external decoder)/-	■/-
Housing	Weather rating	IP68	IP68	IP68
	Vandal resistant	IK10	IK10	IK10
	Operating temperature	-40° to 60° C (-40° to 140° F)	-40° to 60° C (-40° to 140° F)	-40° to 60° C (-40° F to 140° F)

* The hybrid functionality offers an easy migration path from legacy CCTV to a modern IP-based system ** IP features are possible when using optional MIC-IP-PSU Power Supply

IP Video

Digital Recording

All-in-one solution
►DIVAR IP 3000
►DIVAR IP 7000 2U
►DIVAR IP 7000 3U


■ Available – Not available

Commercial Type Number		DIP-304x-xxx	DIP-718x-xxx	DIP-71Fx-xxx
Basic functions	Max. system size	32	128	128
	Integrated video management	■	■	■
	RAID Level	–	RAID-5, RAID-6	RAID-5, RAID-6
	Supported resolutions	CIF/2CIF/4CIF/720p/1080p/5MP	CIF/2CIF/4CIF/720p/1080p/5MP/UHD	CIF/2CIF/4CIF/720p/1080p/5MP/UHD
	Video compression	H.264, MPEG-4, ONVIF, RTSP, JPEG	H.264, MPEG-4, ONVIF, RTSP, JPEG	H.264, MPEG-4, ONVIF, RTSP, JPEG
	Transcoding	■	■	■
	ONVIF	■	–	■
Mechanical	Form factor	4-bay Mini-Tower	2U 19-inch Rack Mount	3U 19-inch Rack Mount
	Network connections (LAN)	1x Gigabit Ethernet	2x Gigabit Ethernet, 1x 100Mbit (Mgmt)	2x Gigabit Ethernet, 1x 100Mbit (Mgmt)
	USB ports	4x USB 2.0/1x USB 3.0	4x USB 2.0, 2x USB 3.0	4x USB 2.0, 2x USB 3.0
	Number of power supplies	1	2	2
	Power supplies hot swappable	–	■	■
	Video output	Connector type	1 DVI, 1 VGA	4x mini-DP (one mini-DP to VGA adapter included)
Spotmonitor		1 per IP decoder, 2nd video output (VGA)	3x via local mini-DP, 1 per IP decoder	3x via local mini-DP, 1 per IP decoder
Audio	In/out channels	32 (audio playback via remote station only)	128	128
	Compression type	G.726	G.726	G.726
	Synchronous audio	■	■	■
	Associate multiple cameras to 1 Audio	■	■	■
Recording	Video Recording Manager (VRM)	■	■	■
	Schedule recording modes	■	■	■
Storage options	Max. drives supported	4	8	16
	Available capacities per drive	2 TB	3 or 4 TB	3 or 4 TB
	Base system capacity TB	0, 4 or 8 TB	0, 12, 16, 24 or 32 TB	0, 48 or 64 TB
	Max. Base system capacity TB	8 TB	32 TB	64 TB
	Full system capacity TB	24 TB	288 TB	320 TB
	Extensible/external support	iSCSI	iSCSI	iSCSI
Storage extensions	Max. number of units	2x DIVAR IP 2000	4x DIVAR IP 6000	4x DIVAR IP 6000
	Maximum drives supported	4	4, 6 or 8	16
	Available capacities per drive	2 TB	3 or 4 TB	3 or 4 TB
	Hot swappable	–	■	■
Export/back-up of data	Data format	WMF, Bosch ASF	native, MOV	native, MOV
	Built-in DVD writer	–	■	■
	Supported devices	External CD/DVD Writer, USB 2.0, USB 3.0, iSCSI	USB 2.0, USB 3.0, iSCSI, internal CD/DVD Writer	USB 2.0, USB 3.0, iSCSI, internal CD/DVD Writer
	Back-up mode	Manual or Automatic	Manual or Automatic	Manual or Automatic

Table continued on the next page

IP Video

Digital Storage

Network Video Recorder

►DIVAR IP 5000

►DIVAR IP 6000 2U

►DIVAR IP 6000 3U

►DSA E-Series



■ Available – Not available

Commercial Type Number		DIP-504xxx-xxx	DIP-618x-xxx	DIP-61Fx-xxx	DSA-Nxxxxx-xxxx
Basic functions	Max. system size	32	128	128	600
	Integrated video management	—	—	—	—
	RAID Level	RAID-1	RAID-5, RAID 6	RAID-5	RAID-5/RAID-6
	Supported resolutions	CIF/2CIF/4CIF/720p/1080p/5MP	CIF/2CIF/4CIF/720p/1080p/5MP/UHD	CIF/2CIF/4CIF/720p/1080p/5MP/UHD	CIF/2CIF/4CIF/720p/1080p/5MP
	Video compression	H.264, MPEG-4, ONVIF, RTSP, JPEG	H.264, MPEG-4, ONVIF, RTSP, JPEG	H.264, MPEG-4, ONVIF, RTSP, JPEG	H.264, MPEG-4, ONVIF, RTSP, JPEG
	Transcoding	■	■	■	—
	ONVIF	■	■	■	■
Mechanical	Form factor	4-bay Mini-Tower	2U 19-inch Rack Mount	3U 19-inch Rack Mount	2U 19-inch Rack Mount
	Network connections (LAN)	2x Gigabit Ethernet	2x Gigabit Ethernet, 1x 100Mbit (Mgmt)	2x Gigabit Ethernet, 1x 100Mbit (Mgmt)	2x Gigabit Ethernet/ 2x 10 Gigabit Ethernet
	USB ports	4x USB 3.0	4x USB 2.0, 2x USB 3.0	4x USB 2.0, 2x USB 3.0	—
	Number of power supplies	1	2	2	2
	Power supplies hot swappable	—	■	■	■
Video output	Connector type	—	VGA	VGA	—
	Spotmonitor	—	1 per IP decoder	1 per IP decoder	—
Audio	In/out channels	32 (audio playback via remote station only)	128 (audio playback via remote station only)	128 (audio playback via remote station only)	800 (audio playback via remote station only)
	Compression type	G.726	G.726	G.726	G.726
	Synchronous audio	■	■	■	■
	Associate multiple cameras to 1 Audio	■	■	■	■
Recording	Video Recording Manager (VRM)	■	■ (VRM ready)	■ (VRM ready)	—
	Schedule recording modes	■	■	■	■
Storage options	Max. drives supported	4	8	16	12
	Available capacities per drive	2 or 4 TB	3 or 4 TB	3 or 4 TB	2, 3, 4 or 6 TB
	Base system capacity TB	0, 4, 8 or 16 TB	0, 12, 16, 24 or 32 TB	0, 48 or 64 TB	—
	Max. Base system capacity TB	16 TB	32 TB	64 TB	24/36/48/72 TB
	Full system capacity TB	16 TB	224 TB	256 TB	384/768/1162 TB **
	Extenable/external support	iSCSI	iSCSI	iSCSI	6Gb/s SAS (Copper)
Storage extensions	Max. number of units	—	4x DIVAR IP 6000 2U or 3x DIVAR IP 6000 3u	4x DIVAR IP 6000 2U or 3x DIVAR IP 6000 3u	7/3 **
	Maximum drives supported	—	4, 6 or 8	16	12/60 **
	Available capacities per drive	—	3 or 4 TB	3 or 4 TB	2, 3, 4 or 6 TB **
	Hot swappable	—	■	■	■
Export/back-up of data	Data format	MP4	WMF, Bosch ASF	WMF, Bosch ASF	WMF, Bosch ASF
	Built-in DVD writer	—	■	■	—
	Supported devices	Web download, FTP, Dropbox	USB 2.0, USB 3.0, iSCSI	USB 2.0, USB 3.0, iSCSI	External CD/DVD Writer, USB 2.0, iSCSI
	Back-up mode	manual	manual	manual	manual or automatic
Redundancy	Power supply redundancy	—	■	■	■
	Hot swappable HDD	—	■	■	■

Table continued on the next page

IP Video

Digital Storage

Network Video Recorder
 ▶DIVAR IP 5000 ▶DIVAR IP 6000 1U ▶DIVAR IP 6000 2U ▶DSA E-Series



■ Available – Not available

Commercial Type Number		DIP-504x-xxx	DIP-618x-xxx	DIP-61Fx-xxx	DSA-Nxxxxx-xxxx
Software options	PTZ control	○ *	○ *	○ *	—
	CCTV keyboard support	○ *	○ *	○ *	—
	Admin control	○ *	○ *	○ *	—
	Export options	○ *	○ *	○ *	—
Remote access	Mobile device (smart phone/tablet)	■ Video security app	■ Video security app	■ Video security app	—
	Network	10/100/1000 Ethernet	10/100/1000 Ethernet	10/100/1000 Ethernet	2x 10 Gigabit Ethernet
	Web browser access	■	■	■	—
	Simultaneous accessible users	5	5	5	—
Advanced features support	Forensic search support (metadata)	■	■	■	—
	Webclient	■	—	—	SANtricity
Supported software	Bosch Video Client	■	■	■	—
	Bosch Video Management System	■ (v2.20 or newer)	■ (v6.0 or newer)	■ (v6.0 or newer)	—
	3rd Party software	via RTSP	—	—	—
3rd party integration tools	Optional ATM/POS integration	—	—	—	—
	SDK (IPP)	■	—	—	—

○ * Via Bosch video software

** Up to three high-density shelf expansion units (60 x 6 TB HDD per expansion shelf) to one Dual controller base unit may be connected - CTN:DSA-N2C7X6-12AT

IP Video

Video Software

►Video Management System



■ Available – Not available

Commercial Type Number	BRS (v8.11) including Appliance	BVMS (v6.0) Lite	BVMS (v6.0) Pro
Channel Count	Up to 64 per Station	32 to 64	8 to 200,000
System Architecture Support	Standalone or Peer-to-Peer (200 max.)	Standalone to Client Server	Client Server (one server/2000 cameras) Multi Server (up to 30 servers/10,000 cameras) Multi-System (unlimited servers/cameras)
Full VMS	Recorder + Viewing Client	Full VMS	Full VMS
Software based Video IP Platform	■	■	■
ONVIF for 3rd Party Camera Intergration	■ (with v8.10)	■	■
Multi-site Support (independent systems tied together)	■ (via VPN tunnelled connection)	■	■
Multi-site Support (dispersed system recording, cameras, remote independent client)	Independant Client with VPN or via Web, one site at a time	■	■
Mobile Clients	–	■ MVS license required: 1 license provides up to 20 connections. Multiple servers with MVS	■ MVS license required: 1 license provides up to 20 connections. Multiple servers with MVS per site
Workstations/Clients	5 web connections, 20 clients	2 clients for 32, 4 clients for 64	100 (Client-Server and Multi-Server), Unlimited (Multi-System)
LDAP	■	■	■
COTS (Commercial off the Shelf) for Server/Workstation	■	■	■
Resolution			
HD-ready	■	■	■
SD and HD	■	■	■
SD and HD Decoder support	–	■	■
Monitor Wall Client GUI Support	–	■	■
4K ultra HD support	–	■	■
Encoding			
H.264	■	■	■
MPEG-4	■	■ (via BRS only)	■ (via BRS only)
3rd party camera support	AXIS MPEG-4 (No PTZ), ONVIF 1.02/Profile-S	■ ONVIF 1.02/Profile-S/RTSP and MJPEG	■ ONVIF 1.02/Profile-S/RTSP and MJPEG
Display			
Multi-monitor support	■ (via browser or BVC)	■ (4)	■ (4)
Workstation OS support	Win XP SP3 (32-bit), Win7 (32/64-bit)	Win7, SP1, Win8.1	Win7, SP1, Win8.1
16:9 Monitor support	■	■	■
Mapping	–	■	■
Dynamic cameo scaling	–	–	–
Client dewarping	–	■	■

Table continued on the next page

IP Video
Video Software

▶Video Management System



■ Available – Not available

Commercial Type Number		BRS (v8.11) including Appliance	BVMS (v6.0) Lite	BVMS (v6.0) Pro
Alarm Management	User management	■	■	■
	Digital I/O alarms	■	■	■
	System event alarms	■	■	■
	Motion alarms	■	■	■
	Event response and command scripts	■	■	■
	IVA alarms	■	■	■
	IVA forensic search	–	■	■
	Audio	■	■	■
	Compound events	–	■	■
	Scheduled dependent alarming	■	■	■
	Event allocation to user groups	–	■	■
Control	AUTODOME Intelligent Tracking	–	■	■
	PTZ	■	■	■
	IntuiKey	■ (via BVC only)	■	■
Storage	Virtual matrix	–	■	■
	@edge camera support	–	■	■
	iSCSI	–	■	■
	NVR support	■	■ (BRS)	■ (BRS)
	VRM	–	■	■
	IVA metadata	–	■	■
	Support redundant storage	–	–	■
	DLA Support (Maximum count of VRM servers)	–	■ (5)	■ (125)
Integration	BVMS	■	–	–
	BRS	–	■	■
	DxR 400/600/700	–	■	■
	BVC	■	–	–
	Bosch intrusion panel	■	■ (GV4 and B-series)	■ (GV4 and B-series)
	Access	■	–	–
	OPC	■	■	■
	CLI/CCL	■	■	■
	ATM/POS	■	■	■
	BIS	■	■	■
	Script control for all system functions	–	■	■
	SDK integration into 3rd party SW	■	■	■
	Virtual inputs	■	■	■
	Barco Transform N series	–	■	■
Networking	LAN/intranet	■	■	■
	WAN	■ (via hardware VPN)	■	■
	Remote/Decoupled Client	■	■	■
	Mobile Viewing APP	–	■ (iOS only)	■ (iOS only)
	Web Client	■	■	■

IP Video

Viewing Software

▶Video Security App

▶Video security client

▶Advanced Viewing Client



■ Available – Not available

Commercial Type Number				BVC (v1.7)/Rec@edge
	No. of channels	16	Up to 16	32 per site
	Usage situation	Mobile usage	Stationary and hybrid	Standalone
	Workstation OS support	iOS, Android	Win7, Win8	XP, Vista, Win7,SP1
	Software based Video IP Platform	■	■	■
	Multi-site Support (independent systems tied together)	–	–	–
	Multi-site Support (dispersed system recording, cameras, remote independent client)	–	–	–
Key technologies supported	Dynamic Transcoding	■	■	■
	IVA	■	■	■
	Client side dewarping (panoramic)	– (planned mid 2015)	■	■
	4K ultra HD starlight	–	■	■
Encoding	H.264	■	■	■
	MPEG-4	■	■	■
	3rd party camera support	■ (with VSG)	■ (with VSG)	ONVIF 1.02/Profile-S with DIVAR IP
Viewing	Multi-monitor support	–	–	■ (2)
	Workstation OS support	iOS	Win7, Win8	XP, Vista, Win7,SP1
	16:9 monitor support	n/a	■	■
	Viewing frequency	–	–	–
	Dynamic cameo scaling	■	■	■
Alarm Management	User management	–	–	–
	Digital I/O alarms	–	–	■
	System event alarms	–	–	■
	Motion alarms	–	–	■
	Event response and command scripts	–	–	–
	IVA alarms	–	–	■
	IVA forensic search	■	■	■
	Audio	–	–	■
	Compound events	–	–	–
	Scheduled dependent alarming	–	–	–
	Event allocation to user groups	–	–	–
	Control	AUTODOME Intelligent Tracking	■	■
	PTZ	■	■	■
	IntuiKey	–	–	■ (limited functionality)
	Virtual matrix	–	–	–
Storage	@edge camera support	■	■	■
	iSCSI	■	■	■
	NVR support	–	–	–
	VRM	■	■	■ (via DIVAR IP)
	IVA metadata	■	■	■
	Support redundant storage	–	–	–
	DLA Support (VRM Mode)	■	■	■ (1)
Integration	BRS	–	–	–
	DxR 400/600/700	–	–	■
	Virtual inputs	–	–	■

IP Video

Encoders and Decoders

Encoders
 ▶VIP X1XF E ▶VIP X1XF ▶VIDEOJET X20 XF E ▶VIDEOJET X40 XF E ▶VIDEOJET multi 4000

Decoders
 ▶VIDEOJET decoder 3000 ▶VIDEOJET decoder 8000



■ Available – Not available

Commercial Type Number	VIP-X1XF-E	VIP-X1XF	VJT-X20XF-E	VJT-X40XF-E	VJM-4016	VJD-3000	VJD-8000
Description	Single Channel Video Encoder	Single Channel Premium Encoder	2 Channel H.264 Video Encoder	4 Channel H.264 Video Encoder	16 Channel H.264 Video Encoder	Single/Quad-stream Decoder	4K UHD and MP Video Decoder
Video/Audio							
Camera Inputs	1	1	2	4	16	–	–
Monitor Outputs	–	–	–	–	–	1 of 2 (HDMI, CVBS)	2 (mini DP)
Video Codec	H.264	H.264	H.264 MP H.264 BP	H.264 MP H.264 BP	H.264 High Profile	H.264 M-JPEG, JPEG	H.264, MPEG-4
Max. frames per second (fps)	25/30@4CIF	25/30@4CIF	25/30	25/30	25/30@4CIF	30@1080p (single view) 60@720p (single view) 4x 25/30@4CIF (quad view)	2x 20@12MP 2x 30@4K 4x 60@1080p (single view) 6x 30@1080p 8x 60@720p
Audio In/Out	1/1	1/1	2/1	2/1	2/1	1/1	0/1 (via DP)
Transcoding at the edge	–	–	■	■	–	–	–
Storage							
Type	SD Card	SD Card	CF	CF	–	–	–
Capacity	2 TB	2 TB	2 TB	2 TB	–	–	–
Intelligence							
Direct-to-iSCSI	■	■	■	■	■	–	–
Video Analytics	Motion+	IVA	Motion+	Motion+	Motion+	–	–
Interfaces							
Alarm In	1	2	4	4	4	4	–
Relay Out	1	2	1	1	1	1	–
ONVIF conformant	■	■	■	■	■	–	–
Other							
Keyboard	–	–	–	–	–	■	–
IP Matrix	–	–	–	–	–	■	–

▶Modular Systems



■ Available – Not available

Commercial Type Number	VIP X1600-B	VIP X1600-XFB
Description	Base System	Base System
Bays	4	4
Ethernet	Two 1 Gbps ports (1 front, 1 rear)	Three 1 Gbps ports (2 front, 1 rear)
SFP Fiber Slot	–	■



■ Available – Not available

Commercial Type Number	VIP X1600 XFM4A	VIP X1600 XFM4B
Description	4 Channel H.264 Encoder Module	4 Channel H.264 Encoder Module with Bilinix
Video/Audio		
Camera Inputs	4	4
Video Codec	H.264 MP H.264 BP+ M-JPEG	H.264 MP H.264 BP+ M-JPEG
Max. frames per second (fps)	25/30@4CIF	25/30@4CIF
Audio In/Out	2/1	2/1
Intelligence		
Direct-to-iSCSI	■	■
Video Analytics	IVA	IVA
Interfaces		
Alarm In	4	4
Relay Out	1	1
SFP Fiber Slot	■	■
ONVIF conformant	■	■

IP Video

Transcoders

Transcoders
►VIDEOJET XTC XF



Transcoder/network & alarm interface device
►VIDEOJET connect 7000



■ Available – Not available

Commercial Type Number		VJT-XTCXF	VJC-7000-90
	Description	4 Channel/Dual-stream Transcoder	5 Channel network switch/Single-stream Transcoder
Video/Audio	Camera Inputs	4	1
	Video Codec	H.264 High Profile	H.264 High Profile
	Max. frames per second (fps)	25/30@4CIF	25/30@4CIF
	Audio In/Out	–	1/–
	Transcoding at the edge	■	■
Storage	Type	CF	CF
	Capacity	2 TB	2 TB
Intelligence	Direct-to-iSCSI	–	–
	Video Analytics	–	–
Interfaces	Alarm In	4	4 dry contacts, 2 monitored tamper alarm (With MIC IP 7000)
	Alarm Out	1	3
	Relay Out	–	1 (for washer pump) (with MIC IP 7000)
	Network (PoE)	–	1x 10/100/1000Base-TX
	Network UTP	–	2x 10/100/1000Base-TX
	Network fiber	–	2 SFP Sockets (1000Base-FX)
	Network daisy chain	–	■ (up to 50)
Other	Output power	–	95W HiPoe
	Washer pump control	–	■ (relay)
	Support for daisy-chaining of multiple cameras	–	■

IP Video Flat Panel Monitors

►High Definition



■ Available – Not available

Commercial Type Number		UML-193-90	UML-223-90	UML-273-90	UML-323-90	UML-423-90	UML-463-90	UML-553-90
Display	Type	19" LED	22" LED	27" LED	32" LED	42" LED	46" LED	55" LED
	Max Pixel Resolution	1366 x 768	1920 x 1080	1920 x 1080	1920 x 1080	1920 x 1080	1920 x 1080	1920 x 1080
	Horizontal Resolution	650 TVL	650 TVL	650 TVL	650 TVL	650 TVL	650 TVL	650 TVL
	Aspect Ratio	16:9	16:9	16:9	16:9	16:9	16:9	16:9
	Brightness (cd/m ²)	250	250	300	350	500	450	450
	Contrast Ratio	1000:1	1000:1	3000:1	3000:1	4000:1	3500:1	4000:1
	Backlight	30,000 hours	30,000 hours	30,000 hours	50,000 hours	50,000 hours	50,000 hours	50,000 hours
	Viewing Angle (HxV)	170° x 160°	170° x 160°	178° x 178°				
Composite Video/Audio Loop-through		passive	passive	passive	passive	passive	passive	passive
PC Compatible		■	■	■	■	■	■	■
Connectors	Composite Video (BNC)	–	–	2 (looping video)				
	VGA	■	■	■	■	■	■	■
	DVI-D	■	■	■	■	■	■	■
	HDMI	■	■	■	■	■	■	■
Audio	Input	■	■	■	■	■	■	■
	Speaker	■	■	■	■	■	■	■
Mechanical	Width	448 mm	515 mm	642 mm	745 mm	977 mm	1024 mm	1256 mm
	Height	332 mm*	370 mm*	380 mm	440 mm	570 mm	578 mm	727 mm
	Depth	182 mm*	182 mm*	76 mm	77 mm	83 mm	112 mm	83 mm
	Weight	3.0 kg	3.6 kg	9.1 kg	12.5 kg	20 kg	25 kg	32 kg
Power	Power Supply	integrated	integrated	included	integrated	integrated	integrated	integrated
	Power Consumption	42W	42W	75W	75W	150W	149 w	170W
Misc.	Picture-in-picture	–	–	–	–	–	–	–
	Front Panel Lockout	■	■	■	■	■	■	■
	IR Remote	–	–	–	■	■	■	■
Cables Included	VGA-to-VGA	■	■	■	■	■	■	■
	DVI-to-DVI	■	■	■	■	■	■	■
Mounting	VESA Compliant	■	■	■	■	■	■	■
	Rack-mountable	–	–	–	–	–	–	–
	Table Stand	included	included	included	UMM-LED32-SD	UMM-LED42-SD	UMM-LED46-SD	UMM-LED42-SD
	Fixed Wall Mount	–	–	–	–	ST650	ST650	ST650
	Swivel/Tilt Wall Mount	–	–	UMM-WMT-32	UMM-WMT-32	–	–	–

A Tradition of Quality and Innovation

For over 125 years, the Bosch name stands for quality and reliability. Bosch is the global supplier of choice for innovative technology, backed by the highest standards for service and support.



Bosch Security Systems proudly offers a wide range of security, safety, communications and sound solutions that are relied upon every day in applications around the world, from government facilities and public venues to businesses, schools and homes.

Bosch Security Systems

To learn more about Video Systems please visit www.boschsecurity.com/hdsecurity

© Bosch Security Systems, 2015
Modifications reserved
VS-EH-en-55_F01U560825_12

 www.facebook.com/BoschSecurity

 www.twitter.com/BoschSecurityEU

 www.youtube.com/BoschSecurity