

CleanSeal top entry PU gasket: full equipment



Advantages

- **NEW! Tool-less filter clamping** 100% secured and immediate
- **NEW! Quick grid locking** for immediate access to filter
- **Long lasting reliability and tightness:** robust fully welded construction
- **Easy installation:** unique movable supporting blocks included
- **Large choice of standardized sizes**
- **Complete interchangeable** diffusion plates range

Application: Turbulent airflow in clean rooms

Type: Terminal housing for HEPA/ULPA filters with PU gasket

Construction: Galvanized steel, fully welded seams

Finishing: White epoxy coated RAL 9010

Connection: By ribbed circular inlet continuous welded on top

For Filters: MEGALAM MD/MX/MD PU gasket frame height (66/90/110mm) (to be ordered separately)

Filter Mounting: Tool-less multi-height quick release lever clamp for immediate and secured clamping including gasket compression limiter and filter retainer.

Control equipment: room side access : 1 port for dp or 100%

Housing installation: by removable «universal blocks, for suspension by hangers, or integration into clean room ceiling panels or fitting into T bar grids system

Diffusion plates (to be ordered separately): Flush hinged grids with “credit card” quick locking: Perforated, swirl, 4 ways, adjustable blades

Model Name	Model***	Size* (AxBxH**/Ø)mm	For filters (WxHxD) mm	Volume m ³	Weight kg
Top entry-PU	CL-SW-3P3-P-XX-T-C160-N-00-AAA	392x392x311/160	305x610x66/90/110	0.05	6.7
Top entry-PU	CL-SW-4P4-P-XX-T-C200-N-00-AAA	544x544x311/200	457x457x66/90/110	0.09	10.1
Top entry-PU	CL-SW-4P4-P-XX-T-C250-N-00-AAA	544x544x311/250	457x457x66/90/110	0.09	10.0
Top entry-PU	CL-SW-5P5-P-XX-T-C250-N-00-AAA	595x595x311/250	508x508x66/90/110	0.11	11.3
Top entry-PU	CL-SW-5P5-P-XX-T-C315-N-00-AAA	595x595x311/315	508x508x66/90/110	0.11	11.1
Top entry-PU	CL-SW-6P6-P-XX-T-C250-N-00-AAA	697x697x311/250	610x610x66/90/110	0.15	14.1
Top entry-PU	CL-SW-6P6-P-XX-T-C315-N-00-AAA	697x697x311/315	610x610x66/90/110	0.15	13.9
Top entry-PU	CL-SW-11P5-P-XX-T-C315-N-00-AAA	1195x595x311/315	1108x508x66/90/110	0.22	19.1
Top entry-PU	CL-SW-12P6-P-XX-T-C315-N-00-AAA	1307x697x311/315	1220x610x66/90/110	0.28	22.7
Note 1 (*): including peripheral return THEN ADD 20mm Note 2 (**): including collar height THEN ADD 46mm Note 3 (***): for ordering, replace XX, and select filter frame height: MD for Megalam MD 66mm MX for Megalam MX 90mm MG for Megalam MG 110mm					

As part of our program for continuous improvement, Camfil reserves the right to change specifications without notice.

CleanSeal Product Overview

AVAILABLE DIFFUSERS



PERFORATED (PF)



SWIRL (SW)



FOUR WAY (4W)



ADJUSTABLE (AV)

AVAILABLE CONFIGURATIONS



TOP ENTRY



RECTANGULAR SIDE ENTRY



SIDE ENTRY



SIDE ENTRY

STANDARDIZED DIMENSIONS

FILTER (ext./mm)

305 x 305

457 x 457

508 x 508

610 x 610

1108 x 508

1220 x 610

3P3

4P4

5P5

6P6

11P5

12P6

392 x 392

544 x 544

595 x 595

697 x 697

1195 x 595

1307 x 697

FRAME (ext./mm)

AVAILABLE FOR ALL GASKET TYPES

CleanSeal versions allow customer to chose any type of gaskets DIN, PU or Camfil Gel gaskets.

